

Canopied unit

T Series Generating Sets from 5kVA to 44kVA with weatherproof/acoustic enclosure

Single Phase (230 V) Mitsubishi Engine	kVA (cos0.8)	Dimensions LxWxH (mm)	Weight (kg)	dB (a)@7m	Run time (hours)
T6KM	5.5	1480x760x1030	390	59.0	29.4
T9KM	8.6	1750x775x1230	544	60.4	20.0
T12KM	12.0	1750x775x1230	600	60.7	14.7
T17C2M	17.0	2080x960x1415	810	61.0	20.8
T25C2M	25.0	2080x960x1415	890	63.0	15.2

Three Phase (400/230 V) Mitsubishi Engine	kVA (cos0.8)	Dimensions LxWxH (mm)	Weight (kg)	dB (a)@7m	Run time (hours)
T8K	7.5	1480x760x1030	400	59.0	29.4
T12K	11.5	1750x775x1230	535	60.4	20.0
T16K	16.0	1750x775x1230	554	60.7	14.7
T22K	22.0	2080x960x1415	790	61.0	21.3
T33K	33.0	2080x960x1415	890	63.0	16.7
T44K	44.0	2080x960x1415	920	61.1	13.7

J Series Generating Sets from 22kVA to 440kVA with weatherproof/acoustic enclosure

Three Phase (400/230 V) John Deere Engine	kVA (cos0.8)	Dimensions LxWxH (mm)	Weight (kg)	dB (a)@7m	Run time (hours)
J22	22.0	2080x960x1415	950	65.0	19.2
J33	33.0	2080x960x1415	970	65.0	19.2
J44K	44.0	2080x960x1415	1040	63.0	11.9
J66K	66.0	2300x1060x1680	1410	66.0	15.0
J77K	77.0	2300x1060x1680	1530	66.0	15.0
J88K	88.0	2300x1060x1680	1530	70.0	12.9
J110K	110.0	2550x1150x1680	1640	67.0	11.5
J130K	132.0	3508x1200x1830	2160	67.6	18.4
J165K	165.0	3508x1200x1830	2230	68.8	13.6
J200K	200.0	3508x1200x1830	2320	69.0	10.9
J220K	220.0	3508x1200x1830	2390	68.6	10.4
J275K	275.0	4000x1380x2145	3150	69.5	9.7
J300K	303.0	4000x1380x2145	3215	69.5	9.2
J400K	402.0	4475x1410x2430	4220	66.5	7.9
J440K	440.0	4475x1410x2430	4250	66.6	7.9

V Series Generating Sets from 220kVA to 700kVA with weatherproof/acoustic enclosure

Three Phase (400/230 V) Volvo Engine	kVA (cos0.8)	Dimensions LxWxH (mm)	Weight (kg)	dB (a)@7m	Run time (hours)
V220C2	220.0	3510x1200x1830	2490	68.5	10.5
V275C2	275.0	4000x1380x2145	3130	68.0	9.2
V350C2	350.0	4480x1410x24	3980	67.0	9.3
V375CV	375.0	4480x1410x2430	3910	67.0	9.3
V410C2	413.0	4480x1410x2430	4320	70.0	8.5
V440C2	440.0	4480x1410x2430	4320	70.0	7.9
V500C2	500.0	5030x1560x2435	4740	68.0	7.2
V550C2	550.0	5030x1560x2435	4870	68.0	6.6
V630C2	630.0	5030x1690x2660	5300	71.5	7.2
V700C2	700.0	5030x1690x2660	5410	75.0	6.5

Specifications

Specifications are subject
to change without notice

Options

Extended autonomy fuel tanks
Comprehensive service plans

Open units

Three phase (400/230 V) John Deere Engine	kVA (cos0.8)	Dimensions LxWxH (mm)	Weight (kg)	Tank (Litres)
J22	22	1700x890x1220	720	100
J33	33	1700x890x1220	740	100
J44K	44	1700x890x1220	820	100
J66K	66	18700x999x1360	1000	180
J77K	77	18700x999x1360	1110	180
J88K	88	1870x999x1360	1110	180
J110K	110	1950x1080x133	1240	190
J130K	132	2370x1110x148	1570	340
J165K	165	2370x1110x148	1640	340
J200K	200	2370x1110x148	1730	340
J220K	220	2370x1110x148	1790	340
J275K	275	2900x1300x1700	2170	390
J300K	303	2900x1300x1680	2235	390
J400K	402	3160x1340x1790	3090	470
J440K	440	3160x1340x1790	3120	470
V220C2	220	2370x1110x1540	1850	340
V275C2	275	2900x1300x1660	2200	390
V350C2	350	3160x1340x1760	2850	470
V375C2	375	3160x1340x1760	2780	470
V410C2	413	3160x1340x1810	3190	470
V440C2	440	3160x1340x1810	3238	470
V500C2	500	3470x1630x2040	3490	500
V550C2	550	3470x1630x2040	3620	500
V630C2	630	3470x1630x2080	3780	610
V700C2	700	3470x1630x2080	3890	610

Uninterruptible Power Supplies Limited

Bacchus House, Calleva Park,
Aldermaston, Berkshire RG7 8EN

T. 0118 981 5151

F. 0118 981 5152

E. sales@upspower.co.uk

W. www.upspower.co.uk